

Product Specifications

Model		NF-8508		
Cable type		CAT5/CAT6		
Voltage protection		60V		
Battery		Type C charge		
Transmitter	CONT	Wiremap Port	RJ45	
		MAX range	300m	
		STP/NTP	✓	
		Digital mode and Analog mode	✓	
	Scan	Frequency	455KHz	
	Port Flash	Full duplex / Half duplex	Automatic Identification	
		Auto-Nego / Non-Auto- Nego		
		10m/100m/1000m		
	Length	≤20M+/-1.6M, 20M~100M+/-2.4M, ≥100M+/-3.2M		
	PoE	Standard/Non standard	Automatic Identification	
		End connection /Middle jumper / Powered by 8 cores		
		PoE Power supply		
	NVL	10Mw		
	Power meter	850/1300/1310/1490/1550/1625 (Wavelength)		
	Crimping	RJ45-8 Cores, Min length is ≥10cm		
Lowervoltage warning	< 3.5V ± 0.1V			
Power supply	3.7V 1500mAh Polymer lithium battery			
Transmitter size	148 X 70 X32 mm			
Recevier	Sensitivity adjustable	✓		
	MAX range	300m		
	Digital mode and Analog mode	✓		
	MAX working current	≤300mA		
	NCV	✓		
	Lamp	✓		
	Lower voltage warning	✓		
	Power supply	3.7V 1500mAh Polymer lithium battery		
	Receiver size	198 x 50 x 28 mm		