

Technical indexes:**NF-8601 Transmitter specifications**

Indicator	LCD 320x240 mm, with backlight
Cable test types	STP/UTP 5E,6E network , telephone , coaxial cable.
Max. distance of wiremap	2000 m
Max. distance of tracing	2000m
Max. distance of cable length	1000 m
Min. distance of calibration	10 m
Accuracy	3% (after calibration)
Compatible connectors	RJ11, RJ45, BNC, PING/POE
Cable map indication	LCD (#1-#8)
Battery Type	3.7V lithium battery 1800mAh
Work temperature / humidity	10°C ~ -60°C / 0°C~70°C
Dimension(LxWxD)	173x92x34mm

NF-8601 Receiver specifications

Cable hunting	RJ11, RJ45, BNC
Types of cable	≥ 2 cores
Battery Type	3.7V lithium battery 1800mAh
Dimension(LxWxD)	183x58x35 mm

NF-8601 Remote unit specifications

Compatible connectors	RJ11, RJ45, BNC
Dimension(LxWxD)	106x32x30mm

➕ Accessories Included:

- Built-in battery x 2 set
- Adapted telephone line x 1 set
- Adapted network cable x 1 set
- Cable clips x 1 set
- Charging adaptor x 1 set
- Carry case x 1 set

➕ Attention:

1. Don't connect high voltage live lines to avoid burning out the machine.
2. Put into the right place to avoid hurting others, because our item with sharp part.
3. Connected the cable to the right port.
4. Read the user manual before use it.